

TracXP™

INDUSTRIAL GAS SOLUTIONS
by Macurco

TracXP is now a part of Macurco Gas Detection, a company that has been providing gas detection solutions for over 45 years. The TracXP line addresses special hazard applications with a comprehensive line of wired and wireless gas detection solutions to meet your most challenging applications.



TXP-FDE UV/IR-HD

Flame Detector by FGD



TXP-FDE UV/IR-HD

The new TracXP TXP-FDE UV/IR-HD flame detector provides an ultra-fast response, high performance, and reliable detection of a broad variety of fires including hydrocarbon fires (visible and non-visible), as well as Hydrogen fires. The UV/IR detector addresses slow-growing fires as well as quickly erupting fires using superior UV/IR technology. The unit operates in all weather and light conditions. The TXP-FDE UV/IR-HD's high definition camera allows clear imaging of fire and personnel at distances up to 100 ft. (30m). Video recording of one-minute pre-event and up to three minutes post-event provides visual documentation of the event. DVR/NVR streaming provides a response team plan of attack information, as well as post-event response review and assessment for training purposes.

Key Features

- Hydrogen and Hydrocarbons flame detection
- High immunity to false alarms
- Ultra-fast detection mode – detection within 5 milliseconds for fireballs or explosions
- High sensitivity – up to 100 ft. (30m) for a 1 ft² (0.1m²) n-heptane pan fire
- HD video output with automatic HD video recording of fire events
- Data / event logger - alarms, faults, etc
- Built-in-test (BIT) automatic & manual self test of window cleanliness & operation (for both IR and UV channels)
- Window heater to avoid condensation & icing

Applications

- Oil & Gas
- Fuel storage facilities & terminals
- Refining & chemical production
- Pipeline compression
- Oil drilling
- Aircraft hangars & maintenance facilities
- Pulp & paper
- Power generation
- Warehousing
- General industry

TXP-FDE UV/IR-HD

Response Data

Fuel Source	Size	Sensitivity	Distance ft. (m)	Avg. Resp. Time(s)
N-Heptane	1x1 ft.	Extreme	262' (80m)	9.0 seconds
N-Heptane	1x1 ft.	Extreme	230' (70m)	4.1 seconds
N-Heptane	1x1 ft.	High	197' (60m)	3.2 seconds
N-Heptane	1x1 ft.	Medium	98' (30m)	1.5 seconds
N-Heptane	1x1 ft.	Low	49' (15m)	1.2 seconds
Gasoline	2x2 ft.	Extreme	328' (100m)	5.3 seconds
Gasoline	1x1 ft.	Extreme	230' (70m)	3.6 seconds
Gasoline	1x1 ft.	Medium	98' (30m)	1.5 seconds
Methane	32-inch plume	Extreme	148' (45m)	3.3 seconds
Methane	32-inch plume	Medium	82' (25m)	0.8 seconds
LPG	32-inch plume	Extreme	180' (55m)	4.8 seconds
LPG	32-inch plume	High	148' (45m)	2.9 seconds
LPG	32-inch plume	Medium	98' (30m)	1.4 seconds
LPG	32-inch plume	Low	49' (15m)	1.4 seconds
Diesel	1x1 ft.	Extreme	164' (50m)	2.9 seconds
Diesel	1x1 ft.	Medium	79' (24m)	3.9 seconds
JP5	2x2 ft.	Extreme	295' (90m)	9.2 seconds
JP5	1x1 ft.	High	164' (50m)	5.8 seconds
JP5	1x1 ft.	Medium	148' (45m)	4.9 seconds
JP5	1x1 ft.	Low	79' (24m)	1.9 seconds
Kerosene	1x1 ft.	Extreme	164' (50m)	4.1 seconds
Kerosene	1x1 ft.	Medium	79' (24m)	2.5 seconds
Ethanol	1x1 ft.	Extreme	125' (38m)	4.2 seconds
Ethanol	1x1 ft.	Medium	75' (23m)	1.6 seconds
Isopropanol	1x1 ft.	Extreme	180' (55m)	3.5 seconds
Isopropanol	1x1 ft.	Medium	75' (23m)	1.0 seconds
Paper	1x1 ft.	Extreme	79' (24m)	0.9 seconds
Paper	1x1 ft.	Medium	39' (12m)	0.8 seconds



Since 1972 Macurco has been providing gas detection solutions for various applications. Macurco provides the highest quality gas detection solutions to customers worldwide.



Macurco Gas Detection
3601 N St. Paul Ave,
Sioux Falls, SD 57104

Phone: 1-877-367-7891

Website: www.macurco.com

Email: info@macurco.com

TXP-FDE UV/IR-HD



False Alarm Immunity

False Alarm Source	Modulated		Un-Modulated	
	Distance ft. (m)	Response	Distance ft. (m)	Response
Sunlight, Direct, Reflected		No Alarm		No Alarm
Incandescent frosted glass light, 300W	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Fluorescent, 70W (3 x 23.3W)	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Electric Arc	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Arc Welding	7.0 ft. (2.0m)	No Alarm	7.0 ft. (2.0m)	No Alarm
Radiation eater, 1850W	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Quartz Lamp (500W) non-shielded	10.0 ft. (0.6m)	No Alarm	10.0 ft. (0.6m)	No Alarm
Mercury Vapor Lamp (160W x3)	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Exhausts	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Projector LED	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Solenoid Bell	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Soldering Iron	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm
Electric Drill	2.0 ft. (0.6m)	No Alarm	2.0 ft. (0.6m)	No Alarm

Approvals

Explosion Proof	ATEX: II 2 G D Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C IECEx Ex db eb IIB T5 Gb or Ex db IIB T5 Gb -50°C≤Ta≤75°C Ex db eb IIB T4 Gb or Ex db IIB T4 Gb -50°C≤Ta≤85°C FM & FMC Class I, Div. 1, Groups B, C & D; T4 Class I, Zone 1, AEx/Ex db IIB T4 Gb T4 -50°C≤Ta≤85°C T5 -50°C≤Ta≤75°C
Performance	ANSI FM 3260 EN 54-10 (pending)
Functional safety	SIL2, per IEC 61508 (pending)
DNV GL (pending)	Standard DNVGL-CG-0339 for open deck locations Temperature class D; Vibration Class A, B and C
EAC CU TR (pending)	



Since 1972 Macurco has been providing gas detection solutions for various applications. Macurco provides the highest quality gas detection solutions to customers worldwide.



Macurco Gas Detection
 3601 N St. Paul Ave,
 Sioux Falls, SD 57104

Phone: 1-877-367-7891

Website: www.macurco.com

Email: info@macurco.com

TXP-FDE UV/IR-HD



Specifications

Flame Detector Specifications

Flame Detection	Detection time & distance	5ms for fast fire burst or explosion 1.5s for 1 ft2 (0.1m2) pan fire at 0–50 ft. (0–15m) <3s for 1 ft2 (0.1m2) pan fire at 50–100 ft. (15–30m)
	Field of view (IR detection)	90° Horizontal, 75° Vertical
	Built-in-test (BIT)	Automatic and Manual
	Time delay	0 - 30 Seconds
Video Functionality	HD Video	Allows clear imaging of fire & personnel at 100 ft. (30m) distance
	Video recording of alarm events	1 minute pre-event and 3 minutes post-event
	System integration protocol	ONVIF (Open Network Video Interface Forum) Profile S
Electrical Specifications	Operating Voltage	24 VDC nominal (18-32 VDC)
	Current consumption	Standby: 180mA Maximum: 250mA all systems in operation (including window heater)
	Conduit Entries	2x conduit entries 3/4" 14NPT or M25x1.5
	Wiring	12-20AWG (2.5-0.35mm2)
Outputs	Relays	Volt-free contacts rated 2A at 30 VDC Alarm – normally open Fault – normally closed
	0 - 20mA (stepped) current output	3 wire and 4 wire configurations (sink and source)
	Modbus	RTU compatible on RS-485
	Station Indication	Tri-Color LED
	Digital (for video)	IP network IEEE 802.3 10Base-t
	Composite Video	NTSC or PAL
Mechanical Specifications	Size	7.87 x 5.12 x 5.12" (200x130x130mm)
	Weight	Detector (Stainless Steel 316): 9.8 lbs. (4.4 kg) Tilt mount (Stainless Steel 316): 5.4 lbs. (2.4 kg)
Environmental Specifications	Temperature	Operating: -67°F to +167°F (-55°C to +75°C) Option: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	Relative Humidity Ingress	Up to 99% (RH), non-condensing IP66 & 68; (2m, 24 hr.) NEMA 4X & 6P



Since 1972 Macurco has been providing gas detection solutions for various applications. Macurco provides the highest quality gas detection solutions to customers worldwide.



Macurco Gas Detection
3601 N St. Paul Ave,
Sioux Falls, SD 57104

Phone: 1-877-367-7891

Website: www.macurco.com

Email: info@macurco.com