

MACURCO

GAS DETECTION

Florida Boiler Code Carbon Monoxide Code

69A-70.010 Installation Requirements

Carbon Monoxide (CO)

- (1) Where required by subsection 509.211(4), F.S., the installation of carbon monoxide detector devices shall comply with the requirements of NFPA 720, as adopted in rule 69A-70.005, F.A.C.
- (2) Detector devices shall bear the label of a nationally recognized testing laboratory and have been tested and listed as complying with the most recent Underwriters Laboratories, Inc., Standard 2075, as adopted in rule 69A-70.005, F.A.C.
- (3) The requirements herein are in addition to the requirement imposed by subsection 509.211(4), F.S., that states devices shall be integrated with the public lodging establishment's fire detection system or connected to a control unit or combination system that will prevent the boiler from operating until it is reset manually.
- (4) Business owners with boilers required to be inspected in accordance with The Boiler Safety Act, chapter 554, Florida Statutes, must post in the boiler room the "Certificate of Carbon Monoxide Detector Installation <http://www.flrules.org/Gateway/reference.asp?No=Ref-08919>," Form DFS-K3-2170 (effective September 2017), which is hereby adopted and incorporated by reference, must be signed by a state-licensed alarm system contractor, a state-certified electrical contractor, or a state-licensed boiler installer indicating the required detector has been installed and has been integrated with the public lodging establishment's fire detection system or boiler safety circuit as described and required by this rule. A copy of Form DFS-K3-2170 may be obtained by written request to the Bureau of Fire Prevention, Boiler Safety Section, 200 East Gaines Street, Tallahassee, Florida 32399-0342..



GD-6
Gas Detector

Gas Boiler
Controller

CM-6
CO Detector

CM-6 KEY FEATURES

- 0-200 PPM range
- Digital display / onboard buzzer
- 2 onboard relays to disable & engage horn/strobes
- Easy installation to 4x4 box
- End of life notification

GBC KEY FEATURES

- 24V Input
- Shutdown up to 8 boilers individually
- Customize up to 8 10A SPDT relays
- 24VDC driver for horn/strobe

Additional Accessories



**FOR MORE INFORMATION PLEASE CONTACT
BRANDEN DEWING | 605-951-3994 | BDEWING@MACURCO.COM**